



Copperhead® Tracer Wire

TRACER WIRE TYPE		COPPER-CLAD STEEL				SOLID COPPER
		COPPERHEAD SOLOSHOT™ XTREME	COPPERHEAD SOLOSHOT™ EXTRA-HIGH STRENGTH	COPPERHEAD HIGH STRENGTH	COPPERHEAD SUPERFLEX™	
APPLICATION		PIPE BURSTING & EXTREME DIRECTIONAL DRILLING	HORIZONTAL DIRECTIONAL DRILLING	OPEN TRENCH	OPEN TRENCH	OPEN TRENCH
BENEFITS		<ul style="list-style-type: none"> - Strongest, most durable - 1,000 lbs stronger than 3/16 stainless steel and equally flexible - 21% conductive, significantly more than stainless steel - No scrap value - Corrosion resistant - 50 mil HDPE jacket - 100% made in USA 	<ul style="list-style-type: none"> - 6X's the breaking strength of solid copper - Pulls through the first time - No scrap value - Corrosion resistant - 45 mil HDPE jacket - 100% made in USA 	<ul style="list-style-type: none"> - 2X's the breaking strength of solid copper - Strong and flexible - 11% lighter than solid copper - No scrap value - Corrosion resistant - 30/45 mil HDPE jacket - 100% made in USA 	<ul style="list-style-type: none"> - As flexible as solid copper - Light-duty applications - Economical - 11% lighter than solid copper - Low recoil - No scrap value - Corrosion resistant - 30/45 mil HDPE jacket - 100% made in USA 	<ul style="list-style-type: none"> - Flexible - Light-duty applications - Low recoil - Corrosion resistant
AWG SIZE	OUTSIDE DIAMETER	BREAKLOAD	BREAKLOAD	BREAKLOAD	BREAKLOAD	BREAKLOAD
18 AWG	.0403	-----	-----	107 lb	75 lb	45 lb
16 AWG	.0508	-----	-----	144 lb	115 lb	71 lb
14 AWG	.0641	-----	-----	282 lb	194 lb	112 lb
12 AWG	.0808	-----	1150 lb	452 lb	302 lb	180 lb
10 AWG	.1019	-----	2032 lb	684 lb	513 lb	285 lb
8 AWG	.1285	-----	2785 lb	830 lb	-----	450 lb
Stranded	.1875	4700 lb	-----	-----	-----	-----

Copperhead tracer wire is **100% made in the USA**

