



APPLICATION

Prewired tracer wire access point sized right and designed to blend in with the gas meter. **Comes prewired with tracer wire and connected ground rod**.

Easily **clips onto riser casing** with optional riser clip (5 sizes available). Provides easy connection point for a utility locate transmitter to emit a low voltage signal on a tracer wire system. Efficiently connect and disconnect jumper to turn ground off/on as needed to isolate the target line.



Preassembled unit includes:

- Mini Cobra Head/Housing 2-terminal, gray, polypropylene, 2.875" x 1"
- Conduit 20" L, .623" D
- Copperhead® copper-clad steal (CCS) tracer wire (10, 12, or 14 AWG), yellow, 6' L
- Ground Rod 0.5-lb, 12" L, .826" D, magnesium, 6' CCS wire black/red
- · Hardware brass terminals, thumb nuts, jumper; stainless steel faceplate screws
- Riser Clip optional, 5 sizes (see above)

Product Number: MCGR-0.5--***** ** Gauge Options: 10 = 10 AWG, 12 = 12 AWG, 14 = 14 AWG *** Riser Clip Options: 00 = no riser clip 75 = riser casing 1.05 OD 100 = riser casing 1.31 OD 125 = riser casing 1.66 OD 150 = riser casing 1.90 OD 200 = riser casing 2.38 OD



FEATURES AND BENEFITS

- Small size and gray color **blends in** with riser for a clean aesthetic
- Prewired <u>with Ground Rod and</u> <u>Tracer Wire</u> for easy installation
- Protects wire from damage and corrosion
- For new or existing services
- Fits multiple riser casing diameters
- Polypropylene material is durable and maintenance-free
- Brass hardware for maximum conductivity